

Technical Data Sheet

ONDULINE®

Monobloc Nails ONDULINE®

ONDULINE®

Product Definition

Quality carbon steel fully zinc galvanized nail with moulded head integrated washer.
Impact and UV resistant head.

ONDULINE®

Technical Data

Effective length	L_g	63 mm	77 mm	93 mm
Total length	L_n	60 mm	80 mm	100 mm
Wire diameter	D_n	2,7 mm	2,7 mm	3 mm
Head diameter	D_k	22 mm	22 mm	22 mm
Head thickness	K	7 mm	7 mm	7 mm
Color masterbatch	%	±2-3	±2-3	±2-3

Available colors:

ONDULINE® nails are produced in red, green, brown, black and terracotta colors in order to match Onduline sheets colors.

Tools:

Hammer or woodworking adze, knife and gloves.

Packaging:

	60 mm	80 mm	100 mm
Qty of Nails/box:	400	400	400
Box/pallet	250	250	250
Qty of nails/pallet	100.000	100.000	100.000
Weight/pallet	±800 kg	±880 kg	±1160 kg

Onduline Avrasya A.Ş.
Değirmen sokak Nida kule
No:18 Kat: 8 Kozyatağı İstanbul · Türkiye
Telefon: +90 216 384 16 00
www.onduline.com.tr

Onduline®
AVRASYA A.Ş.

Technical Data Sheet

ONDULINE®

Monobloc Nails ONDULINE®

ONDULINE®

General Application Steps

ONDULINE®

1. Fixing should be done always through the top of the corrugations..

General warnings

1. ONDULINE® nails are designed in order to enhance maximum penetration onto the wood which increases the extraction resistance and therefore guarantees secure fixing of the sheets..
2. Use only genuine ONDULINE® fixings
3. Avoid over compressing the corrugation.
4. If the nail is twisted when hammering it should be pulled out and replaced. For pulling out the nail place a block of wood underneath the jaw of the pliers and the nailed sheet in order to prevent any damage to the sheet or cut the head of the nail with pliers and drive a new one into the same hole.
5. Think safety first. Wear PPE

Storage

Protect material from heat and direct sunlight. Do not stack pallets.